

| | | | | |
|--------------------|----------------|------------|-----------|----|
| Aspen Petroleum AB | Date: | 9 May 2009 | Issue No: | 10 |
| Issued by: | Birger Agnetun | Sign.: | | |

Product Specification

| | | | |
|----------|------------------------------|----------|--|
| Product: | Plus High Performance | Art. No: | |
|----------|------------------------------|----------|--|

| Property | Minimum | Maximum | Typical Data | Test Method |
|---------------------------|----------------|---------|----------------|-------------|
| RON | 98 | 100 | 98.3 | ASTM D2699 |
| MON | 92 | 94 | 93.2 | ASTM D2700 |
| Density kg/m ³ | 680 | 720 | 699 | ASTM D4052 |
| Lead Content g/L | - | 0.002 | <0.001 | ASTM D 3237 |
| Benzene % wt | - | 0.1 | <0.01 | ASTM D3606 |
| Aromatic Content % wt | - | 0.5 | <0.1 | ASTM D 5443 |
| Olefin Content % wt | - | 0.5 | <0.1 | ISO 3837 |
| Oxygen Cont % wt | 2.5 | 2.7 | 2.7 | GC |
| Sulphur ppm wt | - | 10 | <1 | ASTM D5453 |
| Copper Corr. | - | 1 | 1A | ISO 2160 |
| Appearance | Clear & Bright | - | Clear & Bright | |
| Dist E70 | 15 | 42 | 24 | ASTM D86 |
| Dist E100 | 47 | 55 | 55 | " |
| T50% °C | 90 | 105 | 98 | " |
| Dist E150 | 75 | - | 96 | " |
| FBP °C | - | 200 | 185 | " |
| Residue % | - | 1 | 1 | " |
| Vapour Pressure DVPE hPa | 550 | 650 | 650 | ASTM D5191 |
| | | | | |